

## **DESCRIPTION and USES**

This product is a professional quality interior latex flat paint that features good hiding, washability, easy no-spatter application and good touch-up. This paint is ideal for use on drywall, plaster and masonry in residential and commercial construction. It can be used as a paint and primer all in one, but in certain situations the use of a primer is recommended to achieve maximum performance.

## **SURFACE PREPARATION**

All surfaces to be primed must be dry and free of dust and dirt, oil or other contamination. Loose and peeling paint must be removed to provide a sound surface. Patching and caulking should be done prior to painting. Prime all unpainted surfaces if necessary with a suitable primer.

## **APPLICATION**

Apply with synthetic bristle brush, roller or airless spray. For airless spray, use .017 - .021 tip adjusting pressure as needed. Back rolling after spray application is recommended. Some surfaces may require two coats to achieve a uniform appearance. Allow at least two hours of dry time between coats. For best results apply at a maximum spread rate of 400 square feet per gallon. Do not apply at temperatures below 55°F.

## **SAFETY INFORMATION**

For complete safety information, refer to the SAFETY DATA SHEET (SDS) for this product.

## **COLORS**

White, all RepcoLite Color Renaissance colors and any custom color.

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

## **TECHNICAL DATA**

<b>Vehicle Type:</b>	Vinyl Acrylic Latex
<b>Density:</b>	12.8 lb/gal
<b>Weight Solids:</b>	58.0%
<b>Volume Solids:</b>	35.3%
<b>Coverage:</b>	300 – 400 SF/Gallon depending on surface porosity
<b>Dry Time:</b>	
<i>Touch:</i>	30 Minutes
<i>Recoat:</i>	2 Hours Allow additional dry time in humid conditions
<b>Primer:</b>	
<i>Drywall:</i>	44310 ELEMENTS Latex Wall Primer 44410 Quick Seal
<i>Plaster:</i>	44110 Prime-All 44313 Quick Sand
<i>Masonry:</i>	44610 Block Filler
<i>Wood:</i>	44110 Prime-All 44010 Pro Flo Primer Undercoater
<i>Steel:</i>	44917 Metl-Clad Gray Metal Primer
<b>VOC:</b>	49.5 g/l
<b>Clean Up:</b>	Water

## **PRODUCT CODE INFORMATION**

43410	ELEMENTS Latex Flat Wall Paint White
43403	ELEMENTS Latex Flat Wall Paint #503 base
43406	ELEMENTS Latex Flat Wall Paint #506 base