



Warehouse Marking Paint

Product Data Sheet

DESCRIPTION and USES

This heavy-duty, high-solids gloss enamel features very fast dry and excellent wear characteristics. It is formulated for use as a line-stripping paint in areas subject to heavy vehicle traffic and frequent cleaning. This product is self-priming and is effective for both interior and exterior use.

SURFACE PREPARATION

All surfaces must be dry, free of dirt, grease, rust and loose paint. When painting over previously painted surfaces, apply a small sample area to test for lifting.

APPLICATION

Best applied with conventional, HVLV or airless spray. Small areas may be rolled or brushed. Thinning this product will bring it out of compliance with current VOC regulations. DO NOT THIN. Do not apply at temperatures above 90° F or below 45° F.

NOTICE:

This product is intended for use by professional applicators.

SAFETY INFORMATION

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

For complete safety information, refer to the SAFETY DATA SHEET for this product.

COLORS

Industrial Yellow

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

TECHNICAL DATA

Finish:	High Gloss
Vehicle Type:	Alkyd Resin
Pigments:	Titanium Dioxide, Color Pigments
Volume Solids:	45%
Coverage:	300 – 400 SF/Gallon (depending on surface and application technique.)
Dry Time:	
<i>Touch:</i>	5 – 10 Minutes
<i>Recoat:</i>	3 – 4 Hours
VOC:	Less than 450 g/l
Clean Up:	Xylene

PRODUCT CODE INFORMATION

47860 Warehouse Marking Paint—Yellow

RepcoLite Paints, Inc.

473 W. 17th St.
Holland, MI 49423
(616) 396-1275

