

### DESCRIPTION AND USES

**Mira-Lac Pre-Catalyzed Lacquer** is a product which offers the ease of application associated with lacquer coupled with performance characteristics similar to conversion varnishes. **Mira-Lac Pre-Catalyzed Lacquer** is a single component system that requires no additional catalyzation. It resists yellowing, meets or exceeds KCMA performance requirements and is recommended for use on fine furniture, interior doors and trim as well as kitchen cabinets.

### SPECIFICATIONS

**SURFACE PREPARATION:** All wood surfaces to be finished must be clean, dry and free of contaminants. Stained surfaces should be allowed adequate dry time before finishing. To ensure coating system integrity in situations where the process involves application over existing finishes or if various brands or types of products will be used in a system, testing adhesion and compatibility on a sample panel is strongly encouraged.

**MATERIAL PREPARATION:** **Mira-Lac Pre-Catalyzed Lacquer** is a single component product that does not require the addition of a catalyst. It is supplied ready-for-spray and does not require thinning. Stir container contents well before use. Keep container closed when not dispensing.

**APPLICATION:** **Mira-Lac Pre-Catalyzed Lacquer** is designed for all types of spray application. Apply 1 coat of **740S Clear Sealer** at 3-4 mils wet film build and topcoat with 1-2 coats of **Mira-Lac Pre-Catalyzed Lacquer**.

**CLEAN UP:** Use **910 Lacquer Thinner** to clean dried product off equipment.

### PRECAUTIONS

This product is intended for use by properly trained professionals in a controlled environment. Always pre-test the product or system on the substrate you will be using and under your line conditions to confirm application suitability and to avoid the need for costly refinishing.

### COMPANION PRODUCTS

- 740 Series Products
- 800 Series Stains, Glazes and Toners
- 400 Series Stains and Fillers
- 910 Lacquer Thinner
- 950 Lacquer Retarder

### PRODUCT CODES

**740S - Sealer**

### TECHNICAL DATA

**VEHICLE TYPE:** Pre-Catalyzed Lacquer

**VOLUME SOLIDS:** 16%

**WEIGHT SOLIDS:** 22%

**DENSITY:** 7.5 lbs/gal

**VOC (Actual):** 4.55 lbs/gal

**VOC (Regulatory):** 679 g/L

**CLEAN UP SOLVENT:** 910 Lacquer Thinner

**COVERAGE:** 250 - 265 square feet at 1 mil dry film thickness.

**DRY TIME:** Dry to touch in 7 minutes. Sand or re-coat in 15 minutes.

**SHELF LIFE:** 1 year shelf life when properly stored.

For complete safety information, refer to the SAFETY DATA SHEET for this product.

**RepcoLite**  
Quality Paint Since 1946

RepcoLite Paints, Inc.  
473 W. 17th St.  
Holland, MI 49423  
(616) 396-1275  
[www.repcolite.com](http://www.repcolite.com)