

DESCRIPTION and USES

This easy to use stain gives a beautiful, clear-toned coloring of wood that enhances its natural color and grain. It dries quickly so that recoating with varnish or lacquer can take place the same day. This stain is recommended for use on interior cabinets, doors, floors, paneling and woodwork.

SURFACE PREPARATION

All surfaces to be stained must be clean and dry. Remove soil and smooth rough surfaces by sanding. This stain works best on new, bare wood. Wood that has been stripped of previous finishes is best stained with Repcolite's TRU HUE Stain.

APPLICATION

May be applied with a brush, pad or spray. Apply a thin coat evenly over the surface, avoiding overlaps. If desired, wipe the stained surface lightly with a lint-free cloth to lighten or even out the color.

CLEAN UP

Clean painting tools immediately after use with warm, soapy water. Wipe up spills before they dry with a damp cloth.

SAFETY INFORMATION

For complete safety information, refer to the Safety Data Sheet for this product.

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. Repcolite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

TECHNICAL DATA

Vehicle Type:	Alkyd
Volume Solids:	28%
Coverage:	500 – 600 SF/Gallon
Dry Time:	4 – 6 Hours to Recoat
VOC:	Less than 550 g/l
Clean Up:	Mineral Spirits (Paint Thinner)

PRODUCT CODE INFORMATION

816	Mira Wood-Pro Penetrating Stain
-----	---------------------------------

Repcolite Paints, Inc.
473 W. 17th St.
Holland, MI 49423
(616) 396-1275
www.repcolite.com