



DESCRIPTION AND USES

Port City Log Cabin Maintenance Coat is a non-pigmented version of Port City Log Cabin Wood Finish. It is intended to be used as a maintenance coat on vertical wood surfaces that have been originally finished with the pigmented (tinted) version of Port City Log Cabin Wood Finish. While it is possible to continue to use the pigmented version of this product for maintenance purposes, in some cases doing so will darken the color which may not be desirable. The Maintenance Coat product contains the same durable alkyd resin system as the pigmented version, but does not contain pigments to affect color. **Port City Log Cabin Maintenance Coat** contains UV light absorbers to help protect the coated surface from fading and discoloration, however it is not as durable in this respect as the pigmented Port City Log Cabin Wood Finish and as such it should not be used by itself and is only recommended as a maintenance coat.

SPECIFICATIONS

SURFACE PREPARATION: All surfaces to be coated must be dry and clean.

APPLICATION: Stir well. Do not thin. On bare wood surfaces, apply one coat. Use a natural bristle brush to apply liberal coats, brushing well in the direction of the wood grain. Do not apply at temperatures below 50°F. Do not apply in direct sunlight or on hot surfaces. Clean tools after use with Paint Thinner (Mineral Spirits).

MAINTENANCE: Maintenance of surfaces coated with this product will vary depending on location, type of surface and other factors. A yearly inspection of the coated surface should be made. Small areas of peeling or flaking should be sanded to remove the failed coating and then touched up with two coats. Over time, cracks may develop in wood surfaces. Apply two coats to these cracks when they become visible. When complete re-coating becomes necessary, usually every 2-3 years, clean the surface by applying a solution made out of 4 oz. Tri-Sodium Phosphate (TSP), 1 quart household bleach, and 3 quarts water. Rinse the solution off the wood with a power washer, being careful not to damage the surface by holding the nozzle too close or using too much pressure.

CLEAN UP: Clean tools and equipment immediately with Paint Thinner (Mineral Spirits).

For complete safety information, refer to the SAFETY DATA SHEET for this product.

PRODUCT CODES

00563 - 5 Gallons
00562 - Gallons
00561 - Quarts

TECHNICAL DATA

VEHICLE TYPE: Alkyd Resin

FINISH: Low Sheen

VOLUME SOLIDS: 43%

WEIGHT SOLIDS: 50%

DENSITY: 7.7 lbs/gal

VOC: 460 g/L

CLEAN UP SOLVENT: Paint Thinner (Mineral Spirits)

COVERAGE: 300 SF/gallon

DRY TIME: Dry to touch in 8 hours.

SHELF LIFE: 1 year shelf life when properly stored.

Port City Paints
1250 9th St.
Muskegon, MI 49440
www.portcitypaints.com

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.